

MATERIAL SAFETY DATA SHEET

MSDS NAME: ATA1120 AQUA-TILE EPOXY - TINT BASE COMP "A"

REVISION DATE: 07/25/02 Printed On: 10/27/03 Time: 03:42 PM
Page Number: 1 of 6

SECTION - I - COMPANY AND PRODUCT IDENTIFICATION

Product Name: ATA1120 AQUA-TILE EPOXY - TINT BASE
COMP "A"

Hazard Rating: Health: 2* Fire: 0 Reactivity: 0 PPI:

Company Identification: INSL-X PRODUCTS CORPORATION
P.O. BOX 694
50 HOLT DR.
STONY POINT NY 10980-0694

Telephone/Fax: (845) 786-5000 (845) 786-5831
CHEMTREC(24 HOURS): (800) 424-9300

Product Class: WATER BASED EPOXY
UN Number:

SECTION II - HAZARDOUS INGREDIENTS INFORMATION

Hazardous Ingredients	CAS Number	WEIGHT%
ETHYLENE GLYCOL MONOPROPYL ETH	2807309	5.41
2 BUTOXYETHANOL (GLYCOL ETHER)	111762	3.34
ACETIC ACID	64197	1.80
DIPROPYLENE GLYCOL METHYL ETHE	34590948	1.42

SECTION III - PHYSICAL DATA

Boiling Point/Range: 212.°F - 408.°F (100.°C - 208.89°C)

Vapor Pressure Range(mmHg): 0.6@ 68.°F (20.°C)
12.0 72.°F (22.22°C)

Evaporation Rate: Slower than n-Butyl Acetate

Vapor Density: Heavier than air

% Volatile Weight: 47.2%

% Volatile by Volume: 63.98%

Specific Gravity: 1.33557

VOC MAX LBS/GAL & GRMS/LTR: 2.50/300.36

SECTION IV - FIRE AND EXPLOSION HAZARD INFORMATION

OSHA Flammability Class: IIIB

Flash Point: Not Applicable

Explosive Range: Not Applicable

FIRE EXTINGUISHING MEDIA: Dry chemical, foam, water fog, carbon

MATERIAL SAFETY DATA SHEET

MSDS NAME: ATA1120 AQUA-TILE EPOXY - TINT BASE COMP "A"

REVISION DATE: 07/25/02 Printed On: 10/27/03 Time: 03:42 PM
Page Number: 2 of 6

dioxide.

UNUSUAL FIRE AND EXPLOSION HAZARDS: Keep this product away from heat sparks, flame, and other sources of ignition. Keep containers closed when not in use. Closed containers may burst when exposed to extreme heat or fire. Toxic gases may form when product is exposed to extreme heat. Product may decompose under fire.

FIRE FIGHTING PROCEDURES: Water may be used to cool and protect exposed containers. Use self-contained breathing apparatus. Water may be ineffective in extinguishing a paint fire. Stream of water may spread the flame. If water is used, fog nozzles are preferable.

HAZARDOUS DECOMPOSITION OR COMBUSTION PRODUCTS: Carbon monoxide, carbon dioxide, oxides of nitrogen, oxygen, peroxides, aldehydes, acids, unidentified organic compounds.

SECTION V - HEALTH HAZARD INFORMATION

INHALATION: If affected, remove to fresh air. If breathing stops, give artificial respiration. Administer oxygen if available. Get immediate medical assistance.

SKIN CONTACT: Flush immediately with plenty of water followed by washing with soap and water. Remove contaminated clothing. Wash contaminated clothing before reuse. If irritation occurs, consult a physician.

EYE CONTACT: Flush immediately with large amounts of water, especially under lids for at least 15 minutes. If irritation or other effects persist, obtain medical assistance.

INGESTION: If swallowed obtain medical assistance immediately.

PRIMARY ROUTE(S) OF EXPOSURE: Inhalation, skin contact, eye contact ingestion, depending on conditions of use. To minimize exposure, follow recommendations for proper use, handling, ventilation, and personal protective equipment.

EFFECTS OF OVEREXPOSURE:

INHALATION: Irritation of respiratory tract. Prolonged inhalation may lead to fatigue, drowsiness, dizziness and/or lightheadedness, headache, loss of coordination, nausea, vomiting, diarrhea, chest pain, coughing, sneezing, difficulty with speech, central nervous system depression, metallic taste, confusion, difficulty of breathing, blood abnormalities, tremors, severe respiratory tract irritation, severe lung irritation or burns, liver damage, kidney damage, neurotoxicity. Sanding dust inhalation may cause lung damage.

SKIN CONTACT: Irritation of skin. Prolonged or repeated contact can cause dermatitis, defatting, allergic response, severe skin irritation or burns. Possible sensitization of skin. Skin contact may result in dermal absorption of component(s) of this product which may cause fatigue, drowsiness, dizziness and/or lightheadedness, headache, loss of coordination, nausea, vomiting, diarrhea, central nervous system depression, blood abnormalities, liver damage, kidney damage.

EYE CONTACT: Irritation of eyes. Prolonged or repeated contact can

MATERIAL SAFETY DATA SHEET

MSDS NAME: ATA1120 AQUA-TILE EPOXY - TINT BASE COMP "A"

REVISION DATE: 07/25/02 Printed On: 10/27/03 Time: 03:42 PM

Page Number: 3 of 6

cause conjunctivitis, tearing of eyes, redness of eyes, severe eye irritation or burns, corneal injury.

INGESTION: Ingestion may cause lung inflammation and damage due to aspiration of material into lungs, fatigue, drowsiness, dizziness and/or lightheadedness, headache, loss of coordination, nausea, vomiting, diarrhea, gastro-intestinal, disturbances, abdominal pain, central nervous system depression, blood abnormalities, burns of themouth, throat, stomach, liver damage, kidney damage, pulmonary edema.

MEDICAL CONDITIONS PRONE TO AGGRAVATION BY EXPOSURE: None generally expected when recommendations for proper use, handling, ventilation, and personal protective equipment are followed.

SECTION VI - STABILITY & REACTIVITY INFORMATION

Stability: This product is stable

Hazardous Polymerization: Hazardous polymerization will not occur

MATERIALS TO AVOID: Oxidizers, acids, bases, amines, ammonium salts, metals, nitric acid, magnesium, lewis acids, caustics, mineral acids.

CONDITIONS TO AVOID: Elevated temperatures, contact with oxidizing agent, sparks, open flame, ignition sources. Freezing.

SECTION VII - ACCIDENTAL RELEASE MEASURES

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED:

Eliminate all sources of ignition. Ventilate area. Avoid breathing vapors. Use appropriate personal protective equipment. Use self-contained breathing apparatus if necessary. Contain spill and remove with inert absorbent. Use non-sparking tools. Use proper containers. Prevent material from entering sewers, natural ways, or soil.

WASTE DISPOSAL: Dispose in accordance with all applicable local, county, state, and federal regulations. Do not incinerate closed containers. If necessary, use only a licensed disposal firm/facility.

SECTION VIII - EXPOSURE CONTROLS/PERSONAL PROTECTION

Occupational Exposure Limits

	ACGIH TLV	ACGIH TLV-C	ACGIH STEL	OSHA STEL	OSHA PEL
ETHYLENE GLYCOL MONOPROPYL ETH	N/est	N/est	N/est	N/est	N/est
2 BUTOXYETHANOL (GLYCOL ETHER)	25.00 PPM	N/est	N/est	N/est	25.00 PPM
ACETIC ACID	10.00 PPM	N/est	15.00 PPM	N/est	10.00 PPM

MATERIAL SAFETY DATA SHEET

MSDS NAME: ATA1120 AQUA-TILE EPOXY - TINT BASE COMP "A"

REVISION DATE: 07/25/02 Printed On: 10/27/03 Time: 03:42 PM
Page Number: 4 of 6

DIPROPYLENE GLYCOL METHYL ETHER

100.00 PPM N/est 150.00 PPM 150.00 PPM 100.00 PPM

GENERAL PRECAUTIONS TO BE TAKEN IN USE: Use only with adequate ventilation. Avoid breathing vapor and spray mist. Avoid contact with skin and eyes. Wash hands after using.
Product may contain substances classified as nuisance particulates that may be at hazardous levels only during sanding or abrading of the dried film.

RESPIRATORY PROTECTION: If personal exposure cannot be controlled below applicable limits by ventilation, wear an appropriate properly fitted organic vapor/particulate respirator approved by NIOSH/MSHA (Canadian z94.4).

When sanding or abrading a dried film, wear a dust/mist respirator approved by NIOSH/MSHA (Canadian z94.4) for dust which may be generated from this product, the underlying product, or the abrasive.

VENTILATION: Provide dilution ventilation or local exhaust to maintain the level of vapors and dust below the applicable limits. Use only non-sparking explosion-proof equipment. Discharge exhaust only in area away from ignition sources.

PERSONAL PROTECTIVE EQUIPMENT: Splash goggles or safety glasses with side shields, impervious gloves, impervious clothing, chemical resistant boots for spill clean up.

HYGIENIC PRACTICES: Wash clothing before reuse. Wash hands before eating, smoking, or using washroom.

HMIS:

RATINGS: Ratings are only suggested. The contractor/employer has the ultimate responsibility to evaluate the hazard that this product represents in the environment in which it is used.

RATING SYSTEM: 0=Minimal, 1=Slight, 2=Moderate, 3=Serious, 4=Severe. *=Chronic effects.

PERSONAL PROTECTIVE EQUIPMENT: This code is left blank. It should be entered by the contractor/employer who is familiar with the actual conditions under which this product is ultimately used.

SECTION IX - HANDLING & STORAGE/SPECIAL PRECAUTIONS

HANDLING AND STORAGE: Store in a cool, dry, and well-ventilated area. Keep away from heat, sparks and open flame. Keep from freezing. Keep containers tightly closed and upright when not in use. Do not puncture nor re-use containers. Transfer only to approved containers with complete and appropriate labeling. Containers should be grounded when pouring.

OTHER PRECAUTIONS: Use only with adequate ventilation. Use appropriate respiratory protection. Do not take internally. Keep out of reach of children. Avoid contact with skin and eyes. Avoid breathing of vapors, spray mist, or sanding dust. Empty containers may contain hazardous residues. Wash hands thoroughly after handling, especially before eating or smoking. If this product is part of a multiple component

MATERIAL SAFETY DATA SHEET

MSDS NAME: ATA1120 AQUA-TILE EPOXY - TINT BASE COMP "A"

REVISION DATE: 07/25/02 Printed On: 10/27/03 Time: 03:42 PM
Page Number: 5 of 6

system, the resulting mixture may have the hazards of all of its parts.

SECTION X - ADDITIONAL INFORMATION

SARA TITLE III SECTION 313 (40CFR372):

This product contains a substance(s) that may be subject to the reporting requirements.

Ingredient Name	CAS Number	Weight %
ETHYLENE GLYCOL MONOPROPYL ETH	2807309	5.41
2 BUTOXYETHANOL (GLYCOL ETHER)	111762	3.34

CALIFORNIA PROPOSITION 65:

This product contains a substance(s) known to the state of California to cause cancer and adverse reproductive toxicity.

Ingredient Name	CAS Number	Weight %
2 BUTOXYETHANOL (GLYCOL ETHER)	111762	3.34

As of the date of this MSDS, all of the components in this product are listed (or are otherwise exempt from listing) on the TSCA inventory. This MSDS complies with OSHA hazard communication standard 29 CFR 1910.1200.

The above information pertains to the products as currently formulated and is based on the information received from raw material suppliers and other sources. We believe, to the best of our knowledge, information and belief, the information contained herein to be accurate and reliable as of the date of this material safety data sheet. However, because the conditions of handling, use, and storage of these materials are beyond our control, we assume no responsibility or liability for personal injury or property damage incurred by the use of these materials and make no warranty, expressed or implied, regarding the accuracy or reliability of the data or results obtained from their use. All materials may present unknown hazards and should be used with caution. the information and recommendations in this material safety data sheet are offered for the users' consideration and examination. It is the responsibility of the user to determine the final suitability of this information and data and to comply with all applicable international, federal, state, and local laws and regulations.

As of the date of this MSDS, all of the components in this product are listed (or are otherwise exempt from listing) on the TSCA inventory. This MSDS complies with OSHA hazard communication standard 29 CFR 1910.1200.

The above information pertains to the products as currently formulated and is based on the information received from raw material suppliers and other sources. It is believed to be reliable. However no warranty

MATERIAL SAFETY DATA SHEET

MSDS NAME: ATA1120 AQUA-TILE EPOXY - TINT BASE COMP "A"

REVISION DATE: 07/25/02 Printed On: 10/27/03 Time: 03:42 PM
Page Number: 6 of 6

is expressed or implied regarding its accuracy and no liability is assumed in connection with any of its use.

CEPA:

All substances in this product are on the Canadian Domestic Substance List.

SARA TITLE III SECTION 304 CERCLA (40CFR302.4):

This product contains a substance(s) subject to release notification.